

**BODY CONES**

Even Cut body cones are manufactured from either aluminum oxide resin bond cloth or non-woven surface conditioning material. Our unique splice is designed to increase life expectancy and allow specialized finishes in the automotive, aircraft and prosthetics industries where precision and durability are a must. Mounted on the appropriate sized mandrel, they are used to polish, deburr and finish irregular contours and tapered openings.

**body cones**

aluminum oxide material

die ref no.	base dia.	slant height	top dia.	grit									pkg qty	
				24	36	40	50	60	80	100	120	180		
202	5/8"	2"	5/16"					39314						100
400	1-1/2"	4"	1"		39329					39201		39202		100
413	1"	4"	1/2"	39218										100
418	1"	4"	5/8"		39203					39337		39204		100
426	1-3/8"	4"	1"	39211	39304	39317				39309	39208	39308		100
427	2"	4"	1-1/2"	39327	39216	81217					39217	80822		100
502	1-3/4"	5-5/8"	1-1/4"	39229	39301	39302	39209	39205	39303	39228	39300			100
550	1-5/16"	4"	1-1/8"	43055										100
588	3"	3-1/2"	2"	39340	39334	39212	39310			39345				100
1592	2"	4"	1"		39315									100
1615	7/8"	3"	3/8"	80834						81208			81099	100
1616	1-3/4"	3-1/2"	3/4"	80809		39338								100

**body cones**

surface conditioning material

die ref no.	base dia.	slant height	top dia.	grit	part no.	pkg qty
380	1-5/8"	3-13/16"	1-1/4"	A/Coarse	42678	50
				A/Medium	42679	50
				A/Fine	42680	50
418	1"	4"	5/8"	A/Medium	42685	50
				A/Coarse	81107	50
455	1-13/16"	4"	5/8"	A/Medium	81138	50
				A/Fine	81089	50
				A/Coarse	42716	50
456	1-3/8"	4"	1-1/4"	A/Medium	81139	50
				A/Fine	81195	50
				A/Coarse	42690	50
457	2"	4"	1-1/2"	A/Medium	42691	50
				A/Fine	81197	50
				A/Coarse	42693	50
502	1-3/4"	5-5/8"	1-1/4"	A/Medium	42694	50
				A/Fine	43056	50
1619	3-5/8"	7-1/8"	1/8"	A/Medium	81233	50
				A/Fine	81232	50

