




MATERIAL SAFETY DATA SHEET



SECTION I - NAME AND PRODUCT

MANUFACTURER Even Cut Abrasive	CONTACT TECHNICAL DEPARTMENT
ADDRESS (CITY, STATE AND ZIP) 850 EAST 72nd ST. CLEVELAND, OH 44103	TELEPHONE (800) 322-4321
TRADE NAME, COMMON NAME, OR SPECIFICATION Specialty products, Emery Cloth	DATE: Dec. 1, 2014
CHEMICAL FAMILY OR PRODUCT TYPE Abrasive product, converted form, Emery Cloth	

SECTION II - COMPOSITION

CHEMICAL NAME	% by Wt	CAS #			
Aluminum Oxide	15-30	1344-28-1			
Iron Oxide Mineral	5-15	1309-37-1			
Limestone	5-15	1317-65-3			
Silica	1-2	7631-86-9			
Titanium Dioxide	.5-1.5	13463-67-7			
Cured Resin	2-15				
Cloth Backing	15-40				

*Maximums are required by OSHA 29 CFR 1910.1200 Hazard Communication Standard.

**Please note that steel, aluminum, and/or die cast hardware may be incorporated in this product. These portions in no way represent a hazard when handled in accordance with the measures below.

SECTION III - PHYSICAL AND CHEMICAL DATA

BOILING POINT	N/A	MELTING POINT	N/A	SPECIFIC GRAVITY	N/A
VAPOR PRESSURE	N/A	% VOLATILE BY VOL.	N/A	VAPOR DENSITY	N/A
EVAPORATION RATE	N/A	SOLUABILITY IN WATER	N/A	SOLUBILITY IN ALCOHOL	N/A
SOLUBILITY IN OTHER SOLVENTS N/A			APPEARANCE AND ODOR Grinding disc affixed with overlapping abrasive flaps		

SECTION IV - FIRE AND EXPLOSION HAZARD

FLASH POINT	N/A	METHOD USED	N/A	FLAMMABLE LIMITS	N/A
EXTINGUISHING MEDIA	Water, Carbon Dioxide, Foam, Dry Chemical				
SPECIAL FIRE FIGHTING PROCEDURE	Fiber and resin binder will burn or decompose; use respiratory protection.				
EXPLOSION POTENTIAL	N/A				

SECTION V - HEALTH, FIRST AID AND MEDICAL DATA

PRIMARY ROUTES OF ENTRY	ACUTE AND CHRONIC HEALTH EFFECTS AND EFFECTS OF OVEREXPOSURE	FIRST AID AND MEDICAL TREATMENT
INHALATION Airborne dust during grinding	ACUTE - May cause coughing, shortness of breath CHRONIC - May effect breathing capacity	Remove to fresh air; obtain first aid or medical assistance as needed
INGESTION Dust during grinding	Dust - No known adverse effects, ingestion not recommended	First aid or medical assistance as needed
SKIN During grinding	Not absorbed through skin - may cause abrasion in use	First aid or medical assistance as needed
EYE Airborne dust during grinding	Dust may irritate eyes	Wash with water; first aid or medical assistance as needed
OTHER HEALTH RISKS During grinding	On some materials, elevated sound levels may be created which may effect hearing	Obtain medical assistance as needed

SECTION VI - CORROSIVITY AND REACTIVITY DATA

STABILITY:	UNSTABLE <input type="checkbox"/>	STABLE <input checked="" type="checkbox"/>	POLYMERIZATION:	MAY OCCUR <input type="checkbox"/>	WILL NOT OCCUR <input checked="" type="checkbox"/>
INCOMPATIBILITY (MATERIALS TO AVOID): N/A					
DECOMPOSITION PRODUCTS: In use, dust and decomposing resin fumes are generated. In most cases, the material removed from work piece will be significantly greater than the coated abrasive product.					
CONDITIONS TO BE AVOIDED: N/A					

SECTION VII - STORAGE, HANDLING AND USE PROCEDURES

NORMAL STORAGE AND HANDLING: Handle with adequate ventilation; See OSHA 29 CFR 1910.94 (ventilation) and OSHA 29 CFR 1910.1000 (air contaminants)	
NORMAL USE: Handle with adequate ventilation; See OSHA 29 CFR 1910.94 (ventilation) and OSHA 29 CFR 1910.1000 (air contaminants), OSHA CFR 1910.213 (P) Sanding Machines & OSHA CFR 1910.243	
TRANSPORTATION: There are no chemicals included in the final product that appear as a "hazardous material" as indicated in the Department of Transportation's document 49 CFR doc 172.101 App. A.	
WASTE DISPOSAL METHOD: Standard landfill methods consistent with Federal, State and Local laws	

SECTION VIII - PERSONAL PROTECTION INFORMATION

RESPIRATORY PROTECTION (SPECIFY TYPE)		As needed, approved dust respirator OSHA 24 CFR 1910.134
X	VENTILATION	LOCAL Recommended
	MECHANICAL (GENERAL)	Recommended
	OTHER	NAIF
	PROTECTIVE GLOVES	Recommended when in use
EYE PROTECTION	Recommended OSHA 29 CFR 1910.133 (Face and Eye Protection)	
OTHER EQUIPMENT	As needed, hearing protection OSHA 29 CFR 1910.215 (Hearing Protection)	
See Sections VI, VII and VIII		
MEASURES TO BE TAKEN DURING REPAIR AND MAINTENANCE OF CONTAMINATED EQUIPMENT		

SECTION IX - SPECIAL PRECAUTIONS

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORAGE Slight formaldehyde or phenolic resin odor from binding system may be released during storage	
OTHER PRECAUTIONS N/A	

N/A = NOT APPLICABLE

NAIF = NO APPLICABLE INFORMATION FOUND

FOR COMPANY USE

The information and recommendations set forth herein are taken from sources believed to be accurate as of the date hereof, however, abrasive solutions group. makes no warranty with respect to the accuracy of the information or the suitability of the recommendations, and assumes no liability to any user thereof.