


MATERIAL SAFETY DATA SHEET



SECTION I - NAME AND PRODUCT					
MANUFACTURER	CONTACT				
Even Cut Abrasive Company	TECHNICAL DEPARTMENT				
ADDRESS (CITY, STATE AND ZIP)	TELEPHONE				
850 EAST 72nd ST. CLEVELAND, OH 44103	(800) 322-4321				
TRADE NAME, COMMON NAME, OR SPECIFICATION	DATE:				
Spiral Bands, A/O Dec. 1, 2014					
CHEMICAL FAMILY OR PRODUCT TYPE					
Abrasive product, Spiral Bands, A/O					

SECTION II - COMPOSITION							
CHEMICAL NAME	%	COMMON NAME	REG*	CAS#	OSHA PERMISSIVE	ACGIH	CARCINOGEN
			(Y/N)		EXPOSURE LIMIT	TLV	(Y/N)
ALUMINUM OXIDE	25-35	ALPHA ALUMINA	Y	1344-28-1	15mg/M3	5mg/M3	N
Al2O3		(Abrasive Grain)			(Total Dust)	(Total Dust)	
Duroplastic Phenol or	65-75	Inert or Nuisance Dust	Y	N/A	15mg/M3	5mg/M3	N
Urea Resin binder,					(Total Dust)	(Total Dust)	
& Inert Backing							

*Maximums are required by OSHA 29 CPR 1910.1200 Hazard Communication Standard.

**Please nnote that steel, aluminum, and/or die cast hardware may be incorporated in this product. These portions in no way represent a hazard when handled in accordance with the measures below.

SECTION III - PHYSICAL AND CHEMICAL DATA					
BOILING POINT	N/A	MELTING POINT	N/A	SPECIFIC GRAVITY	N/A
VAPOR PRESSURE	N/A	% VOLATILE BY VOL.	N/A	VAPOR DENSITY	N/A
EVAPORATION RATE	N/A	SOLUABILITY IN WATER	N/A	SOLUBILITY IN ALCOHOL	N/A
SOLUBILITY IN OTHER SOLVENTS			APPEARANCE AND ODOR		
N/A			Spirally wound	bands of abrasive material	

	SECTION IV - FIRE AND EXPLOSION HAZARD				
FLASH POINT	N/A	METHOD USED	N/A	FLAMMABLE LIMITS	N/A
EXTINGUISHING MEDIA	Water, Ca	rbon Dioxide, Foam, Dry Chen	nical		
SPECIAL FIRE FIGHTING PR	OCEDURE	Fiber and resin binder will	l burn or decompose; u	se respiratory protection.	
EXPLOSION POTENTIAL	N/A				

SECTION V - HEALTH, FIRST AID AND MEDICAL DATA						
PRIMARY ROUTES	ACUTE AND CHRONIC HEALTH EFFECTS	FIRST AID AND				
OF ENTRY	AND EFFECTS OF OVEREXPOSURE	MEDICAL TREATMENT				
INHALATION	ACUTE - May cause coughing, shortness of breath	Remove to fresh air; obtain first aid or medical				
Airborne dust during grinding	CHRONIC - May effect breathing capacity	assistance as needed				
INGESTION	Dust - No known adverse effects,	First aid or medical assistance as needed				
Dust during grinding	ingestion not recommended					
SKIN	Not absorbed through skin - may cause	First aid or medical assistance as needed				
During grinding	abrasion in use					
EYE	Dust may irritate eyes	Wash with water; first aid or medical assistance				
Airborne dust during grinding		as needed				
OTHER HEALTH RISKS	On some materials, elevated sound levels	Obtain medical assistance as needed				
During grinding	may be created which may effect hearing					

	SECTION VI - CORROSIVITY AND REACTIVITY DATA						_	
STABILITY:	UNSTABLE	Ш	STABLE	\square	POLYMERIZATION:	MAY OCCUR	WILL NOT OCCUR	\boxtimes
INCOMPATI N/A	BILITY (MATER	IALS T	O AVOID):					
In use, du		npos	•		generated. In most ca coated abrasive produ		emoved from	
	CONDITIONS TO BE AVOIDED:							
			SECTION \	VII - STC	RAGE, HANDLING AN	ID USE PROCEDL	JRES	

NORMAL STORAGE AND HANDLING:

Handle with adequate ventilation; See OSHA 29 CFR 1910.94 (ventilation) and OSHA 29 CFR 1910.1000 (air contaminants)

NORMAL USE:

Handle with adequate ventilation; See OSHA 29 CFR 1910.94 (ventilation) and OSHA 29 CFR 1910.1000 (air contaminants), OSHA CFR 1910.213 (P) Sanding Machines & OSHA CFR 1910.243

TRANSPORTATION:

There are no chemicals included in the final product that appear as a "hazardous material" as indicated in the Department of Transportation's document 49 CFR doc 172.101 App. A.

WASTE DISPOSAL METHOD:

Standard landfill methods consistent with Federal, State and Local laws

	SECTION VIII - PERSONAL PROTECTION INFORMATION				
RESPIRATORY PROTE	CTION (SPECIFY TYPE)	As needed, approved dust respirator OSHA 24 CFR 1910.134			
VENTILATION	LOCAL	Recommended			
X	MECHANICAL	Recommended			
	(GENERAL)				
	OTHER	NAIF			
PROTECTIVE GLOVES	S Recommended when in use				
EYE PROTECTION	Recommended OSHA 29 CFR 1910.133 (Face and Eye Protection)				
OTHER EQUIPMENT As needed, hearing protection OSHA 29 CFR 1910.215 (Hearing Protection)					
See Sections VI, VII and VIII					
MEASURES TO BE TAKEN DURING REPAIR AND MAINTENANCE OF CONTAMINATED FOLLIPMENT					

MEASURES TO BE TAKEN DURING REPAIR AND MAINTENANCE OF CONTAMINATED EQUIPMEN⁻

SECTION IX - SPECIAL PRECAUTIONS

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORAGE

Slight formaldehyde or phenolic resin odor from binding system may be released during storage

OTHER PRECAUTIONS

N/A

N/A = NOT APPLICABLE

NAIF = NO APPLICABLE INFORMATION FOUND

FOR COMPANY USE

The information and recommendations set forth herein are taken from sources believed to be accurate as of the date hereof, however, abrasive solutions group. makes no warranty with respect to the accuracy of the information or the suitablity of the recommendations, and assumes no liability to any user thereof.